

## Safety data sheet

Issue date: 28-03-2017

Version: 01.00/EU

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name: SkamoWall Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: Glue/adhesive

#### 1.3. Details of the supplier of the safety data sheet

Supplier: Skamol A/S  
Østergade 58  
7900 Nykøbing Mors  
Denmark  
Tel: +45 97721533  
Fax: +45 97724975  
Email: insulation@skamol.dk  
WWW: www.skamol.com

#### 1.4. Emergency telephone number

+45 97721533 (Skamol A/S)

---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

CLP-classification (Regulation (EC) No 1272/2008): Eye Dam. 1; H318 Skin Irrit. 2; H315 STOT SE 3; H335

*Please see section 16 for the full text of H-phrases.*

Most serious harmful effects: Causes serious eye damage. Causes skin irritation. May cause respiratory irritation. Corrosive when mixed.

#### 2.2. Label elements



Signal word: Danger

Contains: Portland Cement

H-phrases: Causes serious eye damage.(H318)  
Causes skin irritation.(H315)  
May cause respiratory irritation.(H335)

If medical advice is needed, have product container or label at hand.(P101)

P-phrases:

Keep out of reach of children.(P102)  
Wear protective gloves/protective clothing/eye protection/face protection.(P280)  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.(P305/351/338)  
Immediately call a POISON CENTER/doctor.(P310-a)  
Dispose of contents/container in accordance with local regulation.(P501-A)

Supplemental information:

Contains a reducing agent which reduces soluble chromium VI. The reducing agent is active when stored in a dry place for 12 months after the stated packing date. When stored in moist conditions, e.g. on construction sites, the chromate neutralisation will wear off. Packing that has been opened should be closed tightly after use, and the product should be used as soon as possible.

2.3. Other hazards

(PBT/vPvB) No assessment required, as the product contains inorganic matter only.

---

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

Registration number	CAS/EC No.	Substance	CLP-classification (Regulation (EC) No 1272/2008)	w/w%	Note
.	65997-15-1-E	Portland Cement	Eye Dam. 1; H318 Skin Irrit. 2, H315	25-50	.
.	266-043-4	.	STOT SE 3; H335	.	.
01-2119486767	68475-76-3-A	Flue dust, portland cement	Eye Dam. 1; H318 Skin Irrit. 2, H315	0,1-1	.
-17	270-659-9	.	STOT SE 3; H335 Skin Sens. 1;H317	.	.
.	.	.	.	.	.

Please see section 16 for the full text of H-phrases.

Other information:

Any letters after the CAS number refer to individual data sets.

---

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

Inhalation: Seek fresh air, wash out mouth with water and blow nose thoroughly. Seek medical advice in case of persistent discomfort.

Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. Seek medical advice in case of persistent discomfort.

Skin: Remove contaminated clothing. Wash the skin thoroughly with water and continue washing for a long time. Seek medical advice in case of persistent discomfort.

Eyes: Open eye wide, remove any contact lenses and flush immediately with water (preferably using eye wash equipment). Seek medical advice immediately. Continue flushing until medical attention is obtained.

Other information:

When obtaining medical advice, show the safety data sheet or label.

**4.2. Most important symptoms and effects, both acute and delayed**

Inhalation of dust is irritating to the upper airways. Irritating to skin – may cause reddening. Eye contact may result in deep caustic burns, pain, tearing and cramping of the eyelids. Risk of serious eye injury and loss of sight.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms. No special immediate treatment required.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media The product is not directly flammable. Choose extinguishing agents based on the surrounding fire.

Unsuitable extinguishing media Do not use water stream, as it may spread the fire.

**5.2. Special hazards arising from the substance or mixture**

The product is not directly flammable. Avoid inhalation of vapour and fumes – seek fresh air.

### 5.3. Advice for firefighters

Wear Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Stay upwind/keep distance from source. Wear gloves. In case of insufficient ventilation, wear respiratory protective equipment. Wear safety goggles.

For emergency responders: In addition to the above: Chemical protective suit equivalent to EN 943-2 is recommended.

### 6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water.

### 6.3. Methods and material for containment and cleaning up

Sweep up/collect spills for possible reuse or transfer to suitable waste containers. Wipe up minor spills with a damp cloth.

### 6.4. Reference to other sections

See section 8 for type of protective equipment. See section 13 for instructions on disposal.

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Use the product under well-ventilated conditions. Running water and eye wash equipment must be available. Wash hands before breaks, before using restroom facilities, and at the end of work.

### 7.2. Conditions for safe storage, including any incompatibilities

Store safely, out of reach of children and away from food, animal feeding stuffs, medicines, etc. Store in a cool, dry place.

### 7.3. Specific end use(s)

None.

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Legal basis: Commission Directive 2000/39/EC (Occupational Exposure Limits). Last amended by Commission Directive 2009/161/EU.

Contains no substances subject to reporting requirements.

### 8.2. Exposure controls

Appropriate engineering controls: Wear the personal protective equipment specified below.

Personal protective equipment, eye/face protection: Wear safety goggles/face protection. Eye protection must conform to EN 166.

Personal protective equipment, skin protection: Wear gloves. Type of material: Nitrile rubber. Breakthrough time has not been determined for the product. Change gloves often. Gloves must conform to EN 374. Wear overalls.

Personal protective equipment, respiratory protection: In case of insufficient ventilation, wear respiratory protective equipment with P2 filter. Respiratory protection must conform to one of the following standards: EN 136/140/145.

Environmental exposure controls: Ensure compliance with local regulations for emissions.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Powder  
Colour: Grey  
Odour: Characteristic  
Odour threshold: No data  
pH (solution for use): >12 Aqueous solution (DIN 19261)

pH (concentrate):	No data
Melting point/freezing point:	No data
Initial boiling point and boiling range:	No data
Flash point:	No data
Evaporation rate:	No data
Flammability (solid, gas):	Not flammable
Upper/lower flammability limits:	No data
Upper/lower explosive limits:	No data
Vapour pressure:	No data
Vapour density:	No data
Relative density:	No data
Solubility:	1,5 g/l
Partition coefficient n-octanol/water:	No data
Auto-ignition temperature:	Not spontaneously flammable
Decomposition temperature:	No data
Viscosity:	No data
Explosive properties:	Non-explosive
Oxidising properties:	No data

## 9.2. Other information

VOC (Volatile organic compounds): 0%

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts under heat generation with the following: Acids.

### 10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Acids.

### 10.6. Hazardous decomposition products

None known.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity - oral:	The product does not have to be classified. Test data are not available.
Acute toxicity - dermal:	The product does not have to be classified. Based on existing data, the classification criteria are deemed not to have been met. 65997-15-1-E: Rabbit: LD50 = >2000 mg/kg
Acute toxicity - inhalation:	The product does not have to be classified. Test data are not available.
Skin corrosion/irritation:	Irritating to skin – may cause reddening. Corrosive when mixed.
Serious eye damage/eye irritation:	Strongly irritating to the eyes, causing reddening and increased tear production. May cause serious eye damage. Corrosive when mixed.
Respiratory sensitisation or skin sensitisation:	The product does not have to be classified. Test data are not available.
Germ cell mutagenicity:	The product does not have to be classified. Test data are not available.
Carcinogenic properties:	The product does not have to be classified. Test data are not available.

Reproductive toxicity:	The product does not have to be classified. Test data are not available.
Single STOT exposure:	Inhalation of dust is irritating to the upper airways. If ingested, can be irritating to mucous membranes of the mouth and gastrointestinal tract.
Repeated STOT exposure:	The product does not have to be classified. Test data are not available.
Aspiration hazard:	The product does not have to be classified. Test data are not available.
Other toxicological effects:	None known.

**SECTION 12: Ecological information**

**12.1. Toxicity**

The product does not have to be classified. Test data are not available.

**12.2. Persistence and degradability**

Non-biodegradable.

**12.3. Bioaccumulative potential**

No bioaccumulation expected.

**12.4. Mobility in soil**

Hardens to a firm, non-mobile mass.

**12.5. Results of PBT and vPvB assessment**

(PBT/vPvB) No assessment required, as the product contains inorganic matter only.

**12.6. Other adverse effects**

The product affects the pH value of the local aquatic environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Avoid discharge to drain or surface water. Collect spills and waste in closed, leak-proof containers for disposal at the local hazardous waste site.

EWC code: Depends on line of business and use, for instance 17 01 06\*mixtures of, or separate fractions of concrete, bricks, tiles and ceramics containing dangerous substances

Hardened cement is non-hazardous waste. Contact the local authorities for instructions on handling. Use the below code for waste registration.

EWC code: Depends on line of business and use, for instance 17 01 07mixtures of concrete, bricks, tiles and ceramics other than those mentioned in 17 01 06

Uncleansed packaging is to be disposed of via the local waste-removal scheme.

**SECTION 14: Transport information**

The product is not covered by the rules for transport of dangerous goods.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

-

---

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: Only for use in the period when the water-soluble chromate level is below 2 mg/kg dry cement.  
The product is comprised by Regulation 1907/2006/EC, Annex XVII concerning restrictions.

#### 15.2. Chemical safety assessment

Chemical safety assessments have been performed for the following substances:  
Flue dust, portland cement

---

### SECTION 16: Other information

Abbreviation explanations: PBT: Persistent, Bioaccumulative and Toxic  
vPvB: Very Persistent and Very Bioaccumulative  
STOT: Specific Target Organ Toxicity

Classification method: Calculation based on the hazards of the known components.

H-phrases: H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.

Training: A thorough knowledge of this safety data sheet should be a prerequisite condition.

Other information: This safety data sheet has been prepared for and applies to this product only. It is based on our current knowledge and the information that the supplier was able to provide about the product at the time of preparation. The safety data sheet complies with applicable law on preparation of safety data sheets in accordance with 1907/2006/EC (REACH) as subsequently changed.

---